# SLOT

## surface type or Suspendant
downlight

Aluminum extrusion body
Aluminium injection heatsink
Tempered Glass
UV protected diffuser
Constant current LED driver
Electrostatic powder coating paint
IP20 / IP44 / IP65 Options
Optional body colors
ENEC Standards

LED | 230V | IP44 IP65 | CRI >80 | 60.000h L80 | McAdam C3

## BASIC OPTIONS

- on/off — on/off Control (No Dimmable)
- 230V AC — Input Voltage 230V/AC
- CRI >80 — Color Rendering Index >80
- 4K — Light Temperature 4000K
- Light Beam 16° / 24° / 46° / 70°
- W — White Body Color

| PRODUCT CODE | W | Height | Lenght | Temp | Lumen* |
|---|---|---|---|---|---|
| SLOT.20.90.N.4.46 | 20 | 170 | 125 | 4000K | 2550 |
| SLOT.30.90.N.4.46 | 30 | 170 | 125 | 4000K | 3900 |
| SLOT.35.90.N.4.46 | 35 | 170 | 125 | 4000K | 4760 |
| SLOT.42.90.N.4.46 | 42 | 170 | 125 | 4000K | 5500 |
| SLOT.55.90.N.4.46 | 55 | 170 | 125 | 4000K | 6900 |

** According to 4000K light temperature*

## CUSTOMIZE OPTIONS

| Dimmable 1-10V | Dimmable PUSH | Dimmable TRIAC | Dimmable DALI | Input Voltage 24V/DC | Light Temperature 3000K | Light Temperature 6500K | IP 65 | Color Rendering Index >90 | Black Body Color | EMERGENCY KIT |
|---|---|---|---|---|---|---|---|---|---|---|
| 1-10V | PUSH | TRIAC | DALI | 24V DC | 3K | 6.5K | IP | CRI >90 | B | G |

## PRODUCT CODING

| Product Name | Product Power | Product Size | | Control System | | | | | Color Temperature | | | Light Beam |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| XX | XX | XX | on/off | 1-10V | PUSH | TRIAC | DALI | | 3K | 4K | 6.5K | |
| XX | XX | XX | N | V | P | T | D | | 3 | 4 | 6 | XX |



## TECHNICAL DRAWINGS




** For different options, please contact our team.*