

LAMP

Wall Mounted
Lighting Texture



Wall light luminaire with a unique style that combines solid shape with sources of remarkable performance.

The proportions and the variety of dimensions make it an element with unlimited applications: reliable and easily inserted in any urban area. The LED light source is shielded and offers considerable visual comfort, lighting without glare and without generating light pollution. It is the ideal solution to complete the urban development. Suitable for adding a touch of elegance to your landscape areas.

Characteristics

Aluminium Injection Body

Electrostatic Powder Paint

Optional RAL Colors

Extra Clear 5mm Tempered Glass

Aluminium PCB

LED with Life Span > 100.000 Hours

CCT tolerance within a 3 step MacAdams ellipse

Corrosion Protection (Optional)

5 Years Warranty

Marine Coating (Optional)

Key Advantages

- High sealing
- Simple for modern designs
- Economic and efficient
- Easy installation
- High performance LED
- High corrosion resistance
- UV Resistant Diffuser


Applications



Exterior



Interior



Corridors



Pathway



Public



Hotels



Facade




Architectural



Ancient

LAMP




Standard Product

Input	220-240V / AC 50-60Hz
Control	On / Off
Optic	Symmetrical
Light Color	4000K
Body Color	7016 Grey
CRI	>82
Protection	IP65
Impact Resistance	IK09
Protection class IEC	Class I
Power factor (min.)	0,90
Weight	0,80 - 1.20 kg
Ambient Temperature	-30°C / +55°C

Available Options

Input	24V / DC
Control	DALI, DIM, DMX
Optic	Symmetrical
Light Color	2200K, 2700K, 3000K, 5000K, 6500K
Body Color	Optional RAL colors
CRI	>90
Protection	IP66 - IP67
Warranty	7-10 Years


Light Colors




Ordering Details

Product Code	Power	Light Color	Lumen
LAMP5.AC.N.4.120.7016	5W	4000K	575
LAMP10.AC.N.4.120.7016	10W	4000K	1150
LAMPE27.20.AC.N.4.120.7016	20W	4000K	1300

Body Colors Options



Beam Angle Options



Product Coding

Product Name	Product Power	Input	Control System	Color Temperature	Light Beam	Body Color
XX	XX	AC DC on/off	1-10V PUSH TRAC DALI	3K 4K 6.5K	XX	XX
XX	XX	AC DC N V P T D		3 4 6	XX	XX