



TAG

LED surface type
wall mounted lighting fixture



TAG combines an elegant shape to radial optics specially designed to ensure the best lighting performance, producing different light effects based on the screen type.

Understated and yet remarkably beautiful, TAG is a prime example of the efficient power of puristic design. Without unnecessary frills; nothing distracts from the focus on the key essentials: powerful, homogeneous light in a perfectly flawless cylindrical form.

Various lumen packages and configurations make these highly adaptable LED outdoor luminaires even more flexible.

Characteristics

Aluminium Injection Body

Electrostatic Powder Paint

Optional RAL Colors

Diffuser Glass

Aluminium PCB

LED with Life Span > 100.000 Hours

CCT tolerance within a 3 step MacAdams ellipse

Corrosion Protection (Optional)

5 Years Warranty

Marine Coating (Optional)

Key Advantages

- Flexible Wall Light
- Economic and efficient
- Easy installation
- High performance LED
- High corrosion resistance
- UV Resistant Diffuser

Applications



Exterior




Facade



Architectural



Ancient




Standard Product

Input	220-240V / AC 50-60Hz
Control	On / Off
Optic	Symmetrical
Light Color	4000K
Body Color	7016 Grey
CRI	>82
Protection	IP65
Impact Resistance	IK09
Protection class IEC	Class I
Power factor (min.)	0,090
Weight	0,80 - 1.20 kg
Ambient Temperature	-30°C / +60°C

Available Options

Input	24V / DC
Control	DALI, DIM, DMX
Optic	Symmetrical
Light Color	2200K, 2700K, 3000K, 5000K, 6500K
Body Color	Optional RAL colors
CRI	>90
Protection	IP66 - IP67
Warranty	7-10 Years

Light Colors




Ordering Details

Product Code	Power	Light Color	Lumen
TAG.5.AC.N.4.30.7016	5W	4000K	425
TAG.8.AC.N.4.30.7016	8W	4000K	680

* For different options, please contact our team.

Body Colors Options



Light Effect



Product Coding

Product Name	Product Power	Input	Control System	Color Temperature	Light Beam	Body Color
XX	XX	AC DC on/off 1-10V	PUSH TRAC DALI	3K 4K 6.5K	XX	XX
XX	XX	AC DC N V P T D				