




PANEL C Slim

600x600

LED recessed type
Slim Clip-in panel lighting



- DKP sheet metal body
- Electrostatic coated
- Highly effective LGP
- UV protected diffuser
- Constant current LED driver
- Electrostatic powder coating paint
- Optional body colors
- ENEC Standards

Made in TURKEY



BASIC OPTIONS

on/off	on/off Control (No Dimmable) Input
230V AC	Voltage 220-240V/AC - 50/60 Hz 5
CRI >80	Color Rendering Index >80
4K	Light Temperature 4000K
▲	Light Beam 120°
●	White Satin Polycarbonate Diffuser
°C	-20°C/+40°C Temperature

PRODUCT CODE	W	Lenght	Temp	Lumen*
PLSC60.40.600.N.4.120	40	600x600	4000K	3640
PLSC60.48.600.N.4.120	48	600x600	4000K	4680

* According to 4000K light temperature


CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Transparent Diffuser	White Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN >90	CRI >90	○	W	E

PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	on/off 1-10V PUSH TRIAC DALI	3K 4K 6.5K	▲
XX	XX	XX	N V P T D	3 4 6	XX

TECHNICAL DRAWINGS



* For different options, please contact our team.