

PANEL Slim 300

LED recessed type

Slim backlight panel lighting fixture



DKP sheet metal body

Electrostatic coated

Highly effective LGP

UV protected diffuser

Constant current LED driver Electrostatic

powder coating paint Optional body

colors

ENEC Standards

Made in TURKEY



BASIC OPTIONS

on/off	on/off Control (No Dimmable) Input
230V AC	Voltage 220-240V/AC - 50/60 Hz 5
CRI > 80	Color Rendering Index > 80
4K	Light Temperature 4000K
△	Light Beam 120°
○	White Satin Polycarbonate Diffuser
°C	-20°C/+40°C Temperature

PRODUCT CODE	W	Lenght	Temp	Lumen*
PLS300.12.275x275.N.4.120	12	275x275	4000K	1000

* According to 4000K light temperature


CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Transparent Diffuser	White Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI > 90	○	W	E

PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	on/off 1-10V PUSH TRIAC DALI	3K 4K 6.5K	△
XX	XX	XX	N V P T D	3 4 6	XX

TECHNICAL DRAWINGS



* For different options, please contact our team.