ELECTI SQUARE SF 75

LED surface type

downlight

Aluminum injection body
High efficiency reflector
Constant current LED driver
Elec rostatic powder coating paint
Optional body colors
ENEC Standards
Made in TURKEY

LED | 230V | IP20 IP40 | CRI >80 | 60.000h L80 | McAdam C3

BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 230V/AC
CRI >80	Color Rendering Index >80
4K	Light Temperature 4000K
	Light Beam 19°, 40°
W	White Body Color

PRODUCT CODE	W	Height	Lenght	Temp	Lumen*
ELECSQSF75.7.75.N.4.19	7	110	75	4000K	770
ELECSQSF75.7.75.N.4.40	7	110	75	4000K	750
ELECSQSF75.10.75.N.4.19	10	110	75	4000K	1070
ELECSQSF75.10.75.N.4.40	10	110	75	4000K	1050
ELECSQSF75.13.75.N.4.19	13	110	75	4000K	1260
ELECSQSF75.13.75.N.4.40	13	110	75	4000K	1241

** According to 4000K light temperature*

REFLECTOR OPTIONS

Chrome | Copper | Gold | Platinium | Black

CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index >90	Black Body Color	Grey Body Color
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI >90	B	G

PRODUCT CODING

Product Name	Product Power	Product Size		Control System						Color Temperature			Light Beam
XX	XX	XX	on/off	1-10V	PUSH	TRIAC	DALI		3K	4K	6.5K	
XX	XX	XX	N	V	P	T	D		3	4	6	XX





TECHNICAL DRAWINGS



** For different options, please contact our team.*