

ELECTI SQUARE SF 115

surface type

downlight



Aluminum injection body
High efficiency reflector
Constant current LED driver
Electrostatic powder coating paint
Optional body colors
ENEC Standards
Made in TURKEY



PRODUCT	CODE	W	Height	Lenght	Temp	Lumen*
ELECSQ115.7.115.N.4.19		7	110	115	4000K	770
ELECSQ115.7.115.N.4.40		7	110	115	4000K	750
ELECSQ115.10.115.N.4.19		10	110	115	4000K	1070
ELECSQ115.10.115.N.4.40		10	110	115	4000K	1050
ELECSQ115.13.115.N.4.19		13	110	115	4000K	1260
ELECSQ115.13.115.N.4.40		13	110	115	4000K	1241
ELECSQ115.20.115.N.4.19		20	110	115	4000K	2300
ELECSQ115.20.115.N.4.40		20	110	115	4000K	2260

* According to 4000K light temperature

BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 230V/AC
GU10	GU10 Socket
CRI >80	Color Rendering Index > 80
4K	Light Temperature 4000K
▲	Light Beam 19°, 40°
w	White Body Color

REFLECTOR OPTIONS




PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX XX XX	XX XX XX	XX XX XX	XX XX XX	XX XX XX	XX XX XX
XX XX XX	XX XX XX	XX XX XX	XX XX XX	XX XX XX	XX XX XX

CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Black Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI >90	B	G

TECHNICAL DRAWINGS



* For different options, please contact our team.