


## Surface type or Suspended downlight



- Aluminum extrusion body
- Aluminium injection heatsink
- Tempered Glass
- UV protected diffuser
- Constant current LED driver
- Electrostatic powder coating paint
- IP20 / IP44 / IP65 Options
- Optional body colors
- ENEC Standards



### BASIC OPTIONS

- on/off Control (No Dimmable)
- 230V AC Input Voltage 230V/AC
- CRI > 80 Color Rendering Index > 80
- 4K Light Temperature 4000K
- Light Beam 24° / 46°
- w White Body Color

PRODUCT CODE	W	Height	Dia	Temp	Lumen*
SIMYAS.7.90.N.4.46	7	150	90	4000K	898
SIMYAS.10.90.N.4.46	10	150	90	4000K	1300


\* According to 4000K light temperature

### CUSTOMIZE OPTIONS


Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	IP 65	Color Rendering Index > 90	Black Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	IP	CRI > 90	B	G

### PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	on/off 1-10V PUSH TRIAC DALI	3K 4K 6.5K	XX
XX	XX	XX	N V P T D	3 4 6	XX



### TECHNICAL DRAWINGS



\* For different options, please contact our team.