

surface type or Suspended
downlight



- Aluminum extrusion body
- Aluminium injection heatsink
- Tempered Glass
- UV protected diffuser
- Constant current LED driver
- Electrostatic powder coating paint
- IP20 / IP44 / IP65 Options
- Optional body colors
- ENEC Standards



BASIC OPTIONS

- on/off Control (No Dimmable)
- 230V AC Input Voltage 230V/AC
- CRI > 80 Color Rendering Index > 80
- 4K Light Temperature 4000K
- Light Beam 16° / 24° / 46° / 70°
- w White Body Color


| PRODUCT CODE | W | Height | Dia | Temp | Lumen* |
|--------------------|----|--------|-----|-------|--------|
| SIMYA.20.90.N.4.46 | 20 | 150 | 125 | 4000K | 2550 |
| SIMYA.30.90.N.4.46 | 30 | 150 | 125 | 4000K | 3900 |
| SIMYA.35.90.N.4.46 | 35 | 150 | 125 | 4000K | 4760 |
| SIMYA.42.90.N.4.46 | 42 | 150 | 125 | 4000K | 5500 |

CUSTOMIZE OPTIONS


| | | | | | | | | | | |
|----------------|---------------|----------------|---------------|----------------------|-------------------------|-------------------------|-------|----------------------------|------------------|---------------|
| Dimmable 1-10V | Dimmable PUSH | Dimmable TRIAC | Dimmable DALI | Input Voltage 24V/DC | Light Temperature 3000K | Light Temperature 6500K | IP 65 | Color Rendering Index > 90 | Black Body Color | EMERGENCY KIT |
| 1-10V | PUSH | TRIAC | DALI | 24V DC | 3K | 6.5K | IP | CRI > 90 | B | G |

PRODUCT CODING

| Product Name | Product Power | Product Size | Control System | Color Temperature | Light Beam |
|--------------|---------------|--------------|------------------------------|-------------------|------------|
| XX | XX | XX | on/off 1-10V PUSH TRIAC DALI | 3K 4K 6.5K | XX |
| XX | XX | XX | N V P T D | 3 4 6 | XX |



TECHNICAL DRAWINGS



* For different options, please contact our team.