



Aluminum injection body
High efficiency reflector
Constant current LED driver
Electrostatic powder coating paint
Optional body colors

LED	230V	IP67	CRI > 80			60.000h L80	McAdam C3	CE	TS
-----	------	------	----------	--	--	-------------	-----------	----	----

BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 230V/AC
CRI > 80	Color Rendering Index > 80
4K	Light Temperature 4000K
	Light Beam 19°, 40°
W	White Body Color

PRODUCT CODE W Height Length Hole Size Temp Lumen*

GRACIL.1.45.N.N.	1	39	Ø39,5	Ø35	4000K	110
GRACIL.2.45.N.N.	2	39	Ø39,5	Ø35	4000K	220
GRACIL.3.45.N.N.	3	39	Ø39,5	Ø35	4000K	330

According to 4000K light temperature

COLOR OPTIONS



White





Black

CUSTOMIZE OPTIONS


Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Black Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI > 90	B	E

PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX XX XX	XX XX XX	XX XX XX	XX XX XX XX XX	XX XX XX	XX XX XX
XX XX XX	XX XX XX	XX XX XX	XX XX XX XX XX	XX XX XX	XX XX XX



TECHNICAL DRAWINGS



* For different options, please contact our team.