

Outdoor surface type
LED Bollard Lighting

Aluminium body
High Efficiency LED Lighting
PMMA acrylic light diffuser
Electrostatic powder paint
High quality silicon gasket
Anchor system
Optional body colors
ENEC Standards
IP65, IK08



BASIC OPTIONS

C/off	on/off Control (No Dimmable)
230V AC	Input Voltage 100-3050V AC 50/60 Hz
CRI >80	Rendering Index >80
B	Light Temperature 4000K
	Black Body Color
	-30°/55° C Temperature

PRODUCT CODE	W	Temp	L	Lumen*
KAR.8.600.AC.N.4.SYM.7016	8W	4000K	600mm	800
KAR.10.600.AC.N.4.SYM.7016	10W	4000K	600mm	1000
KAR.15.800.AC.N.4.SYM.7016	15W	4000K	800mm	1500
KAR.20.800.AC.N.4.SYM.7016	20W	4000K	800mm	2000
KAR.25.1000.AC.N.4.SYM.7016	25W	4000K	1000mm	2500
KAR.30.1000.AC.N.4.SYM.7016	30W	4000K	1000mm	3000
KAR.25.1500.AC.N.4.SYM.7016	25W	4000K	1500mm	2500
KAR.30.1500.AC.N.4.SYM.7016	30W	4000K	1500mm	3000
KAR.35.2000.AC.N.4.SYM.7016	35W	4000K	2000mm	3500
KAR.40.2000.AC.N.4.SYM.7016	40W	4000K	2000mm	4000

CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index >90	All RAL codes
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI >90	B

* According to 4000K light temperature

PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	on/off 1-10V PUSH TRIAC DALI	3K 4K 6.5K	XX
XX	XX	XX	N V P T D	3 4 6	XX

TECHNICAL DRAWINGS

