



Aluminium extrusion body
UV protected diffuser
Constant current LED driver
Electrostatic powder coating paint
Optional body colors
ENEC standards



BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 220-240V/AC, 50-60HZ
CRI >80	Color Rendering Index > 80
4K	Light Temperature 4000K
	Light Beam 120°
	Operating Temperature : -20 / 40 °C
w	White Body Color

PRODUCT CODE	W	Height	Lenght	Temp	Lumen*
KOZAL.13.150.N.4.100	13	70	Ø150	4000K	1625


* According to 4000K light temperature

CUSTOMIZE OPTIONS


Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Optional Body Color	Optional Reflector Color	Emergency KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI >90	B	R	E

PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	on/off 1-10V PUSH TRIAC DALI	3K 4K 6.5K	XX



TECHNICAL DRAWINGS



* For different options, please contact our team.