

# KUBIK P75

LED pendant type

square LED lighting fixture

- Aluminum extruded body
- Anodized coating
- UV protected frosted diffuser
- Adjustable length steel ropes
- Nickel plated brass parts
- Constant current LED driver
- Electrostatic powder coating paint
- Production in different lengths
- Optional body colors
- ENEC Standards



PRODUCT CODE	W	Lenght	Temp	Lumen*
KUBIK.72.650x650.N.4.120	72	650x650	4000K	5976
KUBIK.108.950x950.N.4.120	108	950x950	4000K	8856
KUBIK.144.1250x1250.N.4.120	144	1250x	4000K	11808
KUBIK.52.640x640.N.4.120	52	640x460	4000K	5620
KUBIK.61.740x740.N.4.120	61	740x740	4000K	6190
KUBIK.88.104x104.N.4.120	88	104x104	4000K	9150
KUBIK.153.120x120.N.4.120	153	120x120	4000K	15920
KUBIK.176.200x200.N.4.120	176	200x200	4000K	18420
KUBIK.384.300x300.N.4.120	384	300x300	4000K	40120
KUBIK.256.200x200.N.4.120	256	200x200	4000K	26880
KUBIK.105.120x120.N.4.120	105	120x120	4000K	11088
KUBIK.54.750x750.N.4.120	54	750x750	4000K	5800

\* According to 4000K light temperature

## PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX XX XX	N V P T D	3 4 6	XX		



## BASIC OPTIONS

- on/off on/off Control (No Dimmable) Input
- 230V AC Voltage 220-240V/AC - 50/60 Hz 5
- CRI >80 Color Rendering Index >80
- 4K Light Temperature 4000K
- Light Beam 120°
- White Satin Polycarbonate Diffuser
- B Black Body Color
- °C -20C°/+40C° Temperature

## CUSTOMIZE OPTIONS

- Dimmable 1-10V
- Dimmable PUSH
- Dimmable TRIAC
- Dimmable DALI
- Input Voltage 24V/DC
- Light Temperature 3000K
- Light Temperature 6500K
- Dynamic White
- Color Rendering Index > 90
- Transparent Diffuser
- Differernt Body Color
- EMERGENCY KIT

## TECHNICAL DRAWINGS



\* For different options, please contact our team.