


# MINI GLIT

Outdoor type  
LED Bollard Lighting



The elegant sobriety of the MINI GLIT, combined with state-of-the-art lighting technology, ensures its over-average versatility. It can easily be integrated in just about any architectural environment and fulfils every requirement – lighting paths in compliance with safety standards, used in a row as a light signet, as design-oriented decorative lighting or as a standard guidance system.

Various light distributions, lumen packages, sizes and configurations make these highly adaptable LED outdoor luminaires even more .elbixefl Depending on personal taste and the area of installation, MINI GLIT can be used as a bollard, stack or pole-top luminaire. When the optional luminaire canopy is added to the latter, it produces a symbolic, almost archetypal effect... without losing its characteristically modern simplicity.

## Key Advantages

- Can be easily integrated to many designs
- Economic and efficient
- Easy installation
- High performance LED
- High corrosion resistance

## Characteristics

Aluminium body

Extruded pole

High efficiency LED lighting

PMMA light diffuser

Electrostatic powder paint

High quality silicon gasket

Galvanized metal anchorage

ENEC Standards

3 Step MacAdams

IP66, IK08

## Applications



Landscape




Outdoor



Urban

# MINI GLIT




## Standard Product

Input	210-260V / AC 50-65Hz
Control	On / Off
Optic	Symmetrical
Light Color	4000K
Body Color	7016 Grey
CRI	>80
Protection	IP66
Impact Resistance	IK09
Working Temperature	-30°C / +60°C


## Available Options

Input	24V / DC
Control	DALI, DIM, DMX
Optic	8°, 15°, 30°, 50°, 60°, 70°, 90°, 120°, Asymmetrical
Light Color	3000K, 5000K, 6500K
Body Color	Optional RAL colors
CRI	>90

## Light Colors



## Light Effect




## Ordering Details

Product Code	Power	Light Color	Dimensions	Lumen
Mini GLIT.10.AC.N.4.A.7016	10W	4000K	580x220x180	1410
Mini GLIT.20.AC.N.4.A.7016	20W	4000K	1000x220x180	2500
Mini GLIT.30.AC.N.4.A.7016	30W	4000K	1000x220x180	3400

\* For different options, please contact our team.

## Body Colors Options



## Optional Accessories



IP67  
Junction  
Box

## Product Coding

Product Name		Product Power		Input				Control System				Color Temperature			Light Beam		Body Color
XX	XX	AC	DC	0V/0V	1-30V	PUSH	TRAC	DAU	3K	4K	6.5K	XX	XX	XX	XX		
XX	XX	AC	DC	N	V	P	T	D	3	4	6	XX	XX	XX	XX		