



Aluminum injection body,
 UV protected diffuser,
 High Efficiency Reflector,
 Opal Polystyren/PMMA (Fire-Proof) /
 Microprismatic (3D) Diffuser Types,
 Constant current LED driver,
 Electrostatic powder coating paint,
 Optional body colors,
 ENEC Standards



BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 230V/AC
CRI >80	Color Rendering Index > 80
4K	Light Temperature 4000K
	Light Beam 100°
	White Polystyren Diffuser
w	White Body Color
R	Reflector

PRODUCT CODE	W	Height	Lenght	Hole Size	Temp	Lumen*
REFLEX 4".11.147.N.4.95	11	75	Ø147	Ø130	4000K	900
REFLEX 5".19.173.N.4.95	19	75	Ø173	Ø158	4000K	1830
REFLEX 8".46.229.N.4.95	46	80	Ø229	Ø214	4000K	4606


* According to 4000K light temperature

CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Diffuser Options	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN >90	CRI >90		E

PRODUCT CODING

Product Name	Product Power	Product Size	Control System					Color Temperature			Light Beam
XX	XX	XX	1-10V	PUSH	TRIAC	DALI	3K	4K	6.5K		
XX	XX	XX	N	V	P	T	D	3	4	6	XX



* For different options, please contact our team.

TECHNICAL DRAWINGS

