

- Aluminum extrusion body
- Aluminium injection heatsink
- UV protected diffuser
- Constant current LED driver
- Electrostatic powder coating paint
- IP65 Option
- Optional body colors
- ENEC Standards



## BASIC OPTIONS

- on/off** on/off Control (No Dimmable)
- 230V AC** Input Voltage 230V/AC 50-60 Hz
- CRI > 80** Color Rendering Index > 80
- 4K** Light Temperature 4000K
- ▲** Light Beam 100°
- W** White Body Color
- E** Emergency Kit

## CUSTOMIZE OPTIONS

- Dimmable 1-10V
- Dimmable PUSH
- Dimmable TRIAC
- Dimmable DALI
- Input Voltage 24V/DC
- Light Temperature 3000K
- Light Temperature 6500K
- IP 65
- Color Rendering Index > 90
- Black Body Color




PRODUCT CODE	W	Height	Lenght	Temp	Lumen*
SATU.10.90.N.4.100	10	150	125	4000K	1020
SATU.20.90.N.4.100	20	150	125	4000K	2080
SATU.30.90.N.4.100	30	150	125	4000K	3040


\* According to 4000K light temperature

## PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam						
XX	XX	XX	on/off	1-10V	PUSH	TRAC	DALI	3K	4K	6.5K	▲
XX	XX	XX	N	V	P	T	D	3	4	6	XX



## TECHNICAL DRAWINGS



\* For different options, please contact our team.