


## Standard Product

Input	220-240V / AC 50-60Hz
Control	On / Off
Optic	30°
Light Color	4000K
Body Color	7016 Grey
CRI	>82
Protection	IP66
Impact Resistance	IK09
Protection class IEC	Class I
Power factor (min.)	0,090
Weight	4,4 kg
Ambient Temperature	-30°C / +60°C

## Available Options

Input	24V / DC
Control	DALI, DIM, DMX
Optic	30°, 60°, 90°
Light Color	2200K, 2700K, 3000K, 5000K, 6500K
Body Color	Optional RAL colors
CRI	>90
Protection	IP66 - IP67
Warranty	7-10 Years
Glass	Extra Clear


## Light Colors



## Ordering Details

Product Code	Power	Light Color	Lumen
FIZY.5...2000MM..4.7016	5W	4000K	550
FIZY.8...3000MM.4.7016	8W	4000K	880
FIZY.10...4000MM.4.7016	10W	4000K	1100
FIZY.15...5000MM.4.7016	15W	4000K	1650

## Body Colors Options



## Product Coding

Product Name	Product Power	Input	Control System	Color Temperature	Light Beam	Body Color
XX	XX	AC DC	on/off 1-3 DV PUSH TRAC DALI	3K 4K 6.5K	XX	XX
XX	XX	AC DC	N V P T D	3 4 6	XX	XX

## Beam Angle Options

