

APOLLO BOUNDARY

Outdoor-Surface type
LED Boundary Lighting



Apollo Boundary soft light cone creates strikingly beautiful light patterns and reveals stylistic which finesse, bewitches both owner and spectator. Thanks to Apollo Boundary, stone comes to life and buildings can tell stories. This almost magic effect is due to a very pragmatic approach, namely that extraordinary performance creates extraordinary effects.

The housing made of powder-coated, corrosion-free aluminium forms a uniform and integrated whole, and features a high-quality finish in metallic colours.

Characteristics

Aluminium body
High efficiency LED lighting
Electrostatic powder paint
High quality silicone gasket
Galvanized metal anchorage
LED with Life Span > 100.000 Hours
CCT tolerance within a 3 step MacAdams ellipse
Corrosion Protection
Aluminium PCB
5 Years Warranty
Marine Coating (Optional)
ENEC CerrevirD defiit
Diffuser transparent or opaque

Key Advantages

- Flawless cylindrical form
- Economic and efficient
- Easy installation
- High performance LED
- High corrosion resistance

Applications



Landscape




Outdoor



Urban


APOLLO BOUNDARY




Standard Product

Input	100-305V / AC 50-65Hz
Control	On / Off
Optic	Symmetrical
Light Color	4000K
Body Color	7016 Grey
CRI	>82
Protection	IP66
Impact Resistance	IK09
Protection class IEC	Class I
Power factor (min.)	0,092
Weight	- kg
Ambient Temperature	-30°C / +60°C

Light Colors



Body Colors Options



Light Effect



Optional Accessories



Product Coding

Product Name	Product Power	Input	Control System	Color Temperature	Light Beam	Body Color
XX XX	AC DC	on/off 1-10V	PUSH TRIAC DALI	3K 4K 6.5K	XX	XX
XX XX	AC DC	N V	P T D	3 4 6	XX	XX

Available Options

Input	24V / DC
Control	RGB, DALI, DIM, DMX
Optic	8°, 15°, 30°, 50°, 60°, 70°, 90°, 120°, Asymmetrical
Light Color	2200K, 2700K, 3000K, 5000K, 6500K
Body Color	Optional RAL colors
CRI	>90
Protection	IP67-IP68
Impact Resistance	IK10
Warranty	7-10 Years
Diffuser	Transparent or Opaque

Ordering Details

Product Code	Power	Light Color	Dimensions	Lumen
APOLLOBOU.5.250.AC.N.4.SYM.7016	5W	4000K	100x100 H250mm	660
APOLLOBOU.8.250.AC.N.4.SYM.7016	8W	4000K	100x100 H250mm	1056
APOLLOBOU.10.250.AC.N.4.SYM.7016	10W	4000K	100x100 H250mm	1320
APOLLOBOU.15.250.AC.N.4.SYM.7016	15W	4000K	100x100 H250mm	1980
APOLLOBOU.20.250.AC.N.4.SYM.7016	20W	4000K	100x100 H250mm	2640
APOLLOBOU.25.250.AC.N.4.SYM.7016	25W	4000K	100x100 H250mm	3300
APOLLOBOU.30.250.AC.N.4.SYM.7016	30W	4000K	100x100 H250mm	3960

* For different options, please contact our team.