

BOWL

Outdoor type
LED Bollard Lighting



Bowl bollard soft light cone creates strikingly beautiful light patterns and reveals stylistic hcihwfi nesse,bewitches both owner and spectator. Thanks to Bowl, stone comes to life and buildings can tell stories. This almost magic effect is due to a very pragmatic approach, namely that extraordinary performance creates extraordinary effects.

The housing made of powder-coated, corrosion-free aluminium forms a uniform and integrated whole, and features a high-quality nifinishmetallic colours.

Characteristics

Aluminium body
High efficiency LED lighting
Electrostatic powder paint
High quality silicone gasket
Galvanized metal anchorage
LED with Life Span > 100.000 Hours
CCT tolerance within a 3 step MacAdams ellipse
Corrosion Protection
Aluminium PCB
5 Years Warranty
Marine Coating (Optional)
ENEC CerrevirD defiit
Diffuser transparant or opaque

Key Advantages

- Flawless cylindrical form
- Economic and efficient
- Easy installation
- High performance LED
- High corrosion resistance

Applications



Landscape




Outdoor



Urban


BOWL BOLLARD




Standard Product

Input	100-305V / AC 50-65Hz
Control	On / Off
Optic	Asymmetrical
Light Color	4000K
Body Color	7016 Grey
CRI	>82
Protection	IP66
Impact Resistance	IK09
Protection class IEC	Class I
Power factor (min.)	0,092
Weight	- kg
Ambient Temperature	-30°C / +60°C

Light Colors



Body Colors Options



Light Effect



Optional Accessories



Product Coding

Product Name	Product Power	Input		Control System					Color Temperature			Light Beam	Body Color
XX	XX	AC	DC	on/off	1-10V	PUSH	TRIAC	DALI	3K	4K	6.5K	△	XX
XX	XX	AC	DC	N	V	P	T	D	3	4	6	XX	XX

Available Options

Input	24V / DC
Control	RGB, DALI, DIM, DMX
Optic	8°, 15°, 30°, 50°, 60°, 70°, 90°, 120°, Asymmetrical
Light Color	2200K, 2700K, 3000K, 5000K, 6500K
Body Color	Optional RAL colors
CRI	>90
Protection	IP67-IP68
Impact Resistance	IK10
Warranty	7-10 Years
Diffuser	Transparent or Opaque

Ordering Details

Product Code	Power	Light Color	Dimensions	Lumen
BOWL.8.500.AC.N.4.ASY.7016	8W	4000K	500mm	880
BOWL.12.800.AC.N.4.ASY.7016	12W	4000K	800mm	1320
BOWL.15.800.AC.N.4.ASY.7016	15W	4000K	800mm	1650
BOWL.15.1000.AC.N.4.ASY.7016	15W	4000K	1000mm	1650
BOWL.18.1000.AC.N.4.ASY.7016	18W	4000K	1000mm	1980
BOWL.20.1000.AC.N.4.ASY.7016	20W	4000K	1000mm	2200
BOWL.25.1200.AC.N.4.ASY.7016	25W	4000K	1200mm	2750
BOWL.30.1200.AC.N.4.ASY.7016	30W	4000K	1200mm	3300
BOWL.35.1500.AC.N.4.ASY.7016	35W	4000K	1500mm	3850
BOWL.40.1500.AC.N.4.ASY.7016	40W	4000K	1500mm	4400

* For different options, please contact our team.