

LED Pendant /Surfaced type

LED lighting fixture



- Aluminum extruded body
- Anodized coating
- UV protected frosted diffuser
- Adjustable length steel ropes
- Nickel plated brass parts
- Constant current LED driver
- Electrostatic powder coating paint
- Production in different lengths
- Optional body colors
- ENEC Standarts



BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 220-240V/AC - 50/60 Hz 5
CRI >80	Color Rendering Index >80
4K	Light Temperature 4000K
	Light Beam 120°
	White Satin Polycarbonate Diffuser Black
B	Body Color
°C	-20°C/+40°C Temperature


PRODUCT CODE	W	Lenght	Temp	Lumen
FLORA.20.200.N.4.120	20	200	4000K	2000
FLORA.30.250.N.4.120	30	250	4000K	3000
FLORA.30.300.N.4.120	30	300	4000K	3000
FLORA.40.400.N.4.120	40	400	4000K	4000
FLORA.40.500.N.4.120	40	500	4000K	4000
FLORA.50.500.N.4.120	50	500	4000K	5000
FLORA.60.600.N.4.120	60	600	4000K	6000
FLORA.70.600.N.4.120	70	600	4000K	7000
FLORA.80.700.N.4.120	80	700	4000K	8000
FLORA.90.700.N.4.120	90	700	4000K	9000
FLORA.X.XX.N.4.120	X	XX	4000K	XX

*Custom Lenght

* According to 4000K light temperature

CUSTOMIZE OPTIONS


Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Transparent Diffuser	White Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI > 90		W	E



PRODUCT CODING

Product Name	Product Power	Product Size	Control System				Color Temperature			Light Beam	
XX	XX	XX	on/off	1-10V	PUSH	TRIAC	DALI	3K	4K	6.5K	
XX	XX	XX	N	V	P	T	D	3	4	6	XX

TECHNICAL DRAWINGS



* For different options, please contact our team.