

ALYA

LED surface type
Ceiling/Wall mounted lighting fixture



Having Indoor and outdoor use of ALYA with Polycarbonate case is correct choice for multiple applications such as corridors, tunnels, balconies, rooms, park areas with IP40 protection.

It can have motion sensor, radar or 3H kit as built in. It has clean view with Built-in LED driver 220-230V 50-60Hz.

It can be directly on the wall, ceiling, surface mounted with symmetric light distribution. Emergency lighting functional as interruption of the unswitched phase 3 hours duration in case of emergency.

*Status display with green and red LEDs.

Characteristics

Steel Body

Electrostatic Powder Paint

Optional RAL Colors

Tempered Glass Diffuser

Aluminium PCB

LED with Life Span >100.000 Hours

CCT tolerance within a 3 step MacAdams ellipse

Corrosion Protection (Optional)

5 Years Warranty

Marine Coating (Optional)

Key Advantages

- Glare-free
- Economic and tneicife
- Easy installation
- High performance LED
- High corrosion resistance
- Symmetric Beam
- UV Resistant Diffuser
- Modern Design
- Opal glass diffuser

Applications



Exterior



Interior



Corridors




Public



Facade



Hotels




Standard Product

Input	220-230V/ AC 50-60Hz
Control	On / Off
Optic	120°
Light Color	4000K
Body Color	9016 White
CRI	>82
Protection	IP40
Impact Resistance	IK09
Protection class IEC	Class I
Power factor (min.)	0,090
Weight	1 kg
Ambient Temperature	-30°C / +60°C

Available Options

Input	24V / DC
Control	DALI, DIM, DMX
Light Color	2200K, 2700K, 3000K, 5000K, 6500K
Body Color	Optional RAL colors
CRI	>90
Protection	IP65 - IP67
Warranty	7-10 Years
Glass	Extra Clear

Light Colors



Ordering Details


Product Code	Power	Light Color	Lumen
ALYA.10.AC.N.4.120.9016	10W	4000K	1100
ALYA.15.AC.N.4.120.9016	15W	4000K	1650
ALYA.18.AC.N.4.120.9016	18W	4000K	1980
ALYA.20.AC.N.4.120.9016	20W	4000K	2200
ALYA.26.AC.N.4.120.9016	26W	4000K	2860

* For different options, please contact our team.

Body Colors Options



Beam Angle Options



Product Coding

Product Name	Product Power	Input	Control System	Color Temperature	Light Beam	Body Color
XX XX	AC DC	on/off 1-10V	PUSH TRAC DALI	3K 4K 6.5K	XX	XX
XX XX	AC DC	N V	P T D	3 4 6	XX	XX