

# GLOBE SQUARE

Wall Luminaire  
Surface/Wall or Ceiling Mounted



Simple shapes are often best suited to the environment, and squares and circles have always been examples of harmony and perfection. In GLOBE SQUARE, these characteristics are emphasized by applying a simple frame to the wall, which determines the luminous setautnecca dnaflux objects even when closed.

PMMA Body with no visible screws and hidden installation tools. It is corrosion-free aluminium forms a uniform and integrated whole, and features a high-quality nifinishmetallic colours.

## Characteristics

PMMA Body

PMMA Body

Optional RAL Colors

Aluminium PCB

LED with Life Span > 100.000 Hours

CCT tolerance within a 3 step MacAdams ellipse

Corrosion Protection (Optional)

5 Years Warranty

Marine Coating (Optional)

Emergency Kit (Optional)

## Key Advantages

- Glare-free
- Economic and tneicfife
- Easy installation
- High performance LED
- High corrosion resistance


## Applications



Exterior



Interior



Corridors



Public



Architectural




Hotels



Facade

# GLOBE SQUARE




## Standard Product

Input	220-240V / AC 50-60Hz
Control	On / Off
Optic	120°
Light Color	4000K
Body Color	9005 Black
CRI	>82
Protection	IP65
Impact Resistance	IK09
Protection class IEC	Class I
Power factor (min.)	0,090
Weight	2,73 kg
Ambient Temperature	-30°C / +60°C

## Available Options

Input	24V / DC
Control	DALI, DIM, DMX
Light Color	2200K, 2700K, 3000K, 5000K, 6500K
Body Color	Optional RAL colors
CRI	>90
Protection	IP66 - IP67
Warranty	7-10 Years
Emergency	3H Emergency Kit

## Light Colors




## Ordering Details


Product Code	Power	Light Color	Lumen
GLOBESQUARE.15.AC.N.4.120.9005	15W	4000K	1640
GLOBESQUARE.20.AC.N.4.120.9005	20W	4000K	2250
GLOBESQUARE.30.AC.N.4.120.9005	30W	4000K	3010

\* For different options, please contact our team.

## Body Colors Options



## Beam Angle Options



## Product Coding

Product Name	Product Power	Input	Control System	Color Temperature	Light Beam	Body Color
XX XX	AC DC	N V	P T D	3 4 6	XX XX	XX XX