

NAIK 50

LED surface type

downlight

Aluminum extrusion body

Aluminum heatsink

High reflector efficiency

Constant current LED driver

Electrostatic powder coating paint

Optional body colors

ENEC Standards



PRODUCT	CODE	W	Length	Temp	Lumen
NK50.3.50.N.4.12		3	Ø50	4000K	303
NK50.5.50.N.4.12		5	Ø50	4000K	505
NK50.8.50.N.4.12		8	Ø50	4000K	808
NK50.9.50.N.4.12		9	Ø50	4000K	909
NK50.10.50.N.4.12		10	Ø50	4000K	1010
NK50.12.50.N.4.12		12	Ø50	4000K	1212
NK50.14.50.N.4.12		14	Ø50	4000K	1414

* According to 4000K light temperature

CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Black Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI > 90	B	G

TECHNICAL DRAWINGS






BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 230V/AC
CRI > 80	Color Rendering Index > 82
4K	Light Temperature 4000K
▲	Light Beam 12°, 24°, 36°
W	White Body Color

PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX XX	XX	XX	PUSH, 1-10V, TRIAC, DALI	3K, 4K, 6.5K	XX
XX XX	XX	XX	N V P T D	3 4 6	XX



* For different options, please contact our team.