

NAIK 60

LED surface type
downlight

hblux
LIGHTING

Aluminum extrusion body
Aluminum heatsink
High efficiency reflector
Constant current LED driver
Electrostatic powder coating paint
Optional body colors
ENEC Standards



LED	230V	IP20	CRI >82			60.000h L80	McAdam C3	CE	TSE
-----	------	------	---------	--	--	-------------	-----------	----	-----

PRODUCT	CODE	W	Lenght	Temp	Lumen
NK60.8.60.N.4.12		8	Ø60	4000K	856
NK60.11.60.N.4.12		11	Ø60	4000K	1177
NK60.14.60.N.4.12		14	Ø60	4000K	1498
NK60.16.60.N.4.12		16	Ø60	4000K	1712
NK60.18.60.N.4.12		18	Ø60	4000K	1926
NK60.20.60.N.4.12		20	Ø60	4000K	2140

* According to 4000K light temperature

BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 230V/AC
CRI >80	Color Rendering Index >82
4K	Light Temperature 4000K
	Light Beam 12°,24°,36°
w	White Body Color





CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index >90	Black Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI >90	B	G

PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX XX	XX	XX	PUSH 1-10V TRIAC DALI	3K 4K 6.5K	XX
XX XX	XX	XX	N V P T D	3 4 6	XX

TECHNICAL DRAWINGS



* For different options, please contact our team.