

NAIK 70

LED surface type

downlight

Aluminum extrusion body

Aluminum heatsink

High efficiency reflector

Constant current LED driver

Electrostatic powder coating paint

Optional body colors

ENEC Standards




PRODUCT	CODE	W	Lenght	Temp	Lumen
NK70.8.70.N.4.12		8	Ø70	4000K	856
NK70.11.70.N.4.12		11	Ø70	4000K	1177
NK70.14.70.N.4.12		14	Ø70	4000K	1498
NK70.16.70.N.4.12		16	Ø70	4000K	1712
NK70.18.70.N.4.12		18	Ø70	4000K	1926
NK70.20.70.N.4.12		20	Ø70	4000K	2140
NK70.22.70.N.4.12		22	Ø70	4000K	2354

* According to 4000K light temperature

CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Black Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI >90	B	G

TECHNICAL DRAWINGS






BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 230V/AC
CRI >80	Color Rendering Index >82
4K	Light Temperature 4000K
▲	Light Beam 12°, 24°, 36°
w	White Body Color

PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX XX	XX	XX	PUSH, 1-10V, TRIAC, DALI	3K, 4K, 6.5K	XX
XX XX	XX	XX	N V P T D	3 4 6	XX



* For different options, please contact our team.