



Aluminium extrusion body
UV protected diffuser
Constant current LED driver
Electrostatic powder coating paint
Optional body colors
ENEC standards



BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 220-240V/AC, 50-60HZ
CRI > 80	Color Rendering Index > 82
4K	Light Temperature 4000K
Light Beam 120°	
Operating Temperature : -20 / 40 °C	
W	White Body Color

PRODUCT CODE	W	Height	Lenght	Temp	Lumen*
KOZAXL.18.200.N.4.100	18	65	Ø200	4000K	2070
KOZAXL.20.200.N.4.100	20	65	Ø200	4000K	2300
KOZAXL.23.200.N.4.100	23	65	Ø200	4000K	2645


* According to 4000K light temperature

CUSTOMIZE OPTIONS


Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Optional Body Color	Optional Reflector Color	Emergency KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI > 90	B	R	E

PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	on/off, 1-10V, PUSH, TRIAC, DALI	3K, 4K, 6.5K	XX



TECHNICAL DRAWINGS



* For different options, please contact our team.