



- surface type
- Circular lighting fixture
- Anti-glare optical lens
- Aluminum extruded body
- UV protected diffuser
- Adjustable length steel ropes
- Nickel plated brass parts
- Constant current LED driver
- Electrostatic powder coating paint
- Production in different lengths
- Optional body colors
- ENEC standards




BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 220-240V/AC, 50-60HZ
CRI > 80	Color Rendering Index > 82
4K	Light Temperature 4000K
Light Beam 120°	
Operating Temperature : -20 / 40 °C	
B	Black Body Color


CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Optional Body Color	Emergency KIT	Pendant or Surface Type
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI > 90	B	E	M



* For different options, please contact our team.

TECHNICAL DRAWINGS



PRODUCT CODE	W	Lenght	Temp	Lumen
LOOP LINERESSF.22.400.N.4.120	22	Ø400	4000K	1980
LOOP LINERESSF.30.400.N.4.120	30	Ø400	4000K	2640
LOOP LINERESSF.35.600.N.4.120	35	Ø600	4000K	3145
LOOP LINERESSF.42.600.N.4.120	42	Ø600	4000K	3780
LOOP LINERESSF.50.800.N.4.120	50	Ø800	4000K	4500
LOOPP LINERESF.65.800.N.4.120	65	Ø800	4000K	5850
LOOP LINERESSF.77.1200.N.4.120	77	Ø1200	4000K	6930
LOOP LINERESSF.84.1200.N.4.120	84	Ø1200	4000K	7560
LOOP LINERESSF.90.1500.N.4.120	90	Ø1500	4000K	8600
LOOP LINERESSF.97.1500.N.4.120	97	Ø1500	4000K	8730
LOOP LINERESSF.106.1800.N.4.120	106	Ø1800	4000K	8478
LOOP LINERESSF.119.1800.N.4.120	119	Ø1800	4000K	9519
LOOP LINERESSF.140.1800.N.4.120	140	Ø1800	4000K	12600

* According to 4000K light temperature

PRODUCT CODING

Product Name	Product Power	Product Size	Control System					Color Temperature			Light Beam
XX XX XX	XX XX XX	XX XX XX	on/off	1-10V	PUSH	TRIAC	DALI	3K	4K	6.5K	XX
XX XX XX	XX XX XX	XX XX XX	N	V	P	T	D	3	4	6	XX