


AURA LINE TRACK

Track type lighting fixture

Track mounted

Aluminum extruded body
UV protected diffuser
Diffused Light
Adjustable length steel ropes
Nickel plated brass parts
Constant current LED driver
Electrostatic powder coating paint
Production in different lengths
Optional body colors
ENEC standards



PRODUCT CODE	W	Length	Temp	Lumen*
AURALINE TRACK.10.300.N.4.120	10	300	4000K	1030
AURALINE TRACK.15.300.N.4.120	15	300	4000K	1545
AURALINE TRACK.20.300.N.4.120	20	300	4000K	2060
AURALINE TRACK.25.500.N.4.120	25	500	4000K	2575
AURALINE TRACK.30.500.N.4.120	30	500	4000K	3090
AURALINE TRACK.35.1000.N.4.120	35	1000	4000K	3605
AURALINE TRACK.40.1000.N.4.120	40	1000	4000K	4120
AURALINE TRACK.45.1200.N.4.120	45	1200	4000K	4635
AURALINE TRACK.50.1200.N.4.120	50	1200	4000K	5150
AURALINE TRACK.55.1200.N.4.120	55	1200	4000K	5665

BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 220-240V/AC, 50-60HZ
CRI >80	Color Rendering Index > 82
4K	Light Temperature 4000K
Light Beam 120°	
Operating Temperature : -20 / 40 °C	
B	Black Body Color



CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Optional Body Color	Emergency KIT	Pendant or Surface Type
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI > 90	B	E	M

PRODUCT CODING

Product Name	Product Power	Product Size	Control System					Color Temperature			Light Beam
XX	XX	XX	on/off	1-10V	PUSH	TRIAC	DALI	3K	4K	6.5K	
XX	XX	XX	N	V	P	T	D	3	4	6	XX

TECHNICAL DRAWINGS



* For different options, please contact our team.

www.hb-lux.com

*We reserve the right to change specifications without prior written notice