

LINERES TRACK

Track type lighting fixture

Track mounted

Aluminum extruded body

Optical Lens

Adjustable length steel ropes

Nickel plated brass parts


Constant current LED driver

Electrostatic powder coating paint

Production in different lengths

Optional body colors

ENEC standards



PRODUCT CODE	W	Lenght	Temp	Lumen*
LINERES TRACK.10.300.N.4.50	10	300	4000K	1220
LINERES TRACK.15.300.N.4.50	15	300	4000K	1830
LINERES TRACK.20.300.N.4.50	20	300	4000K	2440
LINERES TRACK.25.500.N.4.50	25	500	4000K	3050
LINERES TRACK.30.500.N.4.50	30	500	4000K	3660
LINERES TRACK.35.1000.N.4.50	35	1000	4000K	4270
LINERES TRACK.40.1000.N.4.50	40	1000	4000K	4120
LINERES TRACK.45.1200.N.4.50	45	1200	4000K	4880
LINERES TRACK.50.1200.N.4.50	50	1200	4000K	6100
LINERES TRACK.55.1200.N.4.50	55	1200	4000K	6710

BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 220-240V/AC, 50-60HZ
CRI >80	Color Rendering Index > 82
4K	Light Temperature 4000K
Light Beam 50°,80°	
Operating Temperature : -20 / 40 °C	
B	Black Body Color


CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Optional Body Color	Emergency KIT	Pendant or Surface Type
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI > 90	B	E	M

PRODUCT CODING

Product Name	Product Power	Product Size	Control System					Color Temperature			Light Beam
XX XX XX	XX XX XX	XX XX XX	on/off	1-10V	PUSH	TRIAC	DALI	3K	4K	6.5K	XX XX XX
XX XX XX	XX XX XX	XX XX XX	N	V	P	T	D	3	4	6	XX

TECHNICAL DRAWINGS



* For different options, please contact our team.

*We reserve the right to change specifications without prior written notice

www.hb-lux.com